

SAFETY DATA SHEET - WHITE CEMENTITIOUS ADHESIVES

CWFTA (White) • RAPIDSET (White) • FASTSET (White) • FASTSET FLEXIBLE (White)

I PART CWFTA (White) • I PART RAPIDSET (White) • MARBLEFIX (White)

ULTIMATEFLEX (White) • MOSAICFIX (White)

Date: 08/08

Issue: 04

Page 1 of 2



1. IDENTIFICATION OF SUBSTANCE/PREPARATION AND COMPANY

Product: All those listed above.
Company: Granfix Products Limited • Greenhill Lane • Riddings • Derbys • DE55 4AT
Telephone: 01773 607778 • Fax: 01773 608688

2. COMPOSITION

Product Classification:
Irritant. Contains more than 20% Portland cement in addition to inorganic fillers and organic additives.

Hazardous Ingredient	Classification	%	Index	Risk Phrases
Portland Cement	CAS No. 65997-15-1 EINECS; 266-043-4	>20	Xi	R38, R41

3. HAZARDS IDENTIFICATION

Hazard designation: Xi Irritant.
Hazard to man and the environment: R38 Irritating to skin.
R41 Risk of serious damage to eyes.

4. FIRST AID MEASURES

Inhalation: If irritation occurs, remove to fresh air. If nose/airways become inflamed, seek medical advice.
Skin: Wash thoroughly with soap and water. Remove contaminated clothing. If irritation, pain or other skin trouble occurs, seek medical advice.
Eyes: Irrigate eyes with clean water for at least 15mins. Obtain medical attention as soon as possible.
Ingestion: Do not induce vomiting. Wash out mouth with water and give plenty of water to drink.
If symptoms develop or persist seek immediate medical advice.

5. FIRE FIGHTING MEASURES

Product is not flammable, neither as powder or when set.

6. ACCIDENTAL RELEASE MEASURES

Wear suitable personal protection measures (dust mask, gloves, goggles).
Recover spillages in dry state if possible, avoid dust formation (See section 8).
Do not allow material into water courses and drains.

7. HANDLING/STORAGE

Avoid skin/eye contact. Use in well ventilated areas, especially when mixing.
Wash hands after use.
Store in cool dry conditions and protect from frost.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Suitable gloves should be worn to prevent skin contact.
If dust formation is likely, a suitable dust mask should be worn.
If splashing is a possibility then goggles should be worn.
Occupational exposure must be kept below 10mg/m³/8hour (TWA).
Total Inhalable Dust: 10mg/m³ Inhalable Dust 4mg/m³ (TWA) Respirable Dust

The information given on this safety data sheet is accurate and given in good faith. However, it is given without guarantee as conditions of use and workmanship are beyond the control of Granfix Products. All information is subject to the company's terms and conditions of sale, copies of which are available on request.

SAFETY DATA SHEET - WHITE CEMENTITIOUS ADHESIVES

CWFTA (White) • RAPIDSET (White) • FASTSET (White) • FASTSET FLEXIBLE (White)

I PART CWFTA (White) • I PART RAPIDSET (White) • MARBLEFIX (White)

ULTIMATEFLEX (White) • MOSAICFIX (White)

Date: 08/08

Issue: 04

Page 2 of 2



9. PHYSICAL/CHEMICAL PROPERTIES

Appearance: Gritty Powders except Mosaicfix - Fine White Powder
Density: 1.6 approx.
Solubility: Slightly soluble
pH: Approximately 12 at 20°C saturated solution

10. STABILITY/REACTIVITY

Stable when stored correctly.
Storage in wet/damp conditions may lead to premature hydration of product.
Avoid contact with strong acids and alkalis.

11. TOXICOLOGICAL INFORMATION

Irritant effect on the skin or mucous membranes.
Strong irritant for eyes.
Can cause serious eye damage.

12. ECOLOGICAL INFORMATION

The addition of this product to water will give an alkaline solution which may be toxic to aquatic life.
Do not allow into water courses/drains.

13. WASTE DISPOSAL

Should be disposed of at a suitable landfill site in accordance with Control of Pollution Act 1974 and the Environmental Protection Act 1990.

14. TRANSPORT INFORMATION

This product is not classed as hazardous for the purposes of transportation.

15. REGULATORY INFORMATION

This product has been classified and labelled in accordance with the directives on hazardous materials.
Classification: Irritant.
Reference: Information from raw material suppliers.
Chemicals (Hazard information and packaging) Regulations 2002: Amended 2003.

Risk Phrases	R38 R41	Irritating to skin Risk of serious damage to eyes.
Safety Phrases	S2 S24/25 S26 S37/39	Keep out of reach of children Avoid contact with eyes and skin In case of contact with eyes, rinse immediately with plenty of water and seek medical advice Wear suitable gloves and eye/face protection

16. OTHER INFORMATION

The product should be used as directed. Consult product data sheet for further details.
This information is given in good faith and is believed to be accurate and complete.
It should be made available to all personnel handling this product.

The information given on this safety data sheet is accurate and given in good faith. However, it is given without guarantee as conditions of use and workmanship are beyond the control of Granfix Products. All information is subject to the company's terms and conditions of sale, copies of which are available on request.

SAFETY DATA SHEET - GREY CEMENTITIOUS ADHESIVES

CWFTA • RAPIDSET • FASTSET • FASTSET FLEXIBLE • 1 PART CWFTA • 1 PART RAPIDSET
PORCELAINFIX • POURABLE THICK BED • SLATEFIX • ULTIMATEFLEX
UNIQUE BLUE • UNIQUE RED

Date: 08/08

Issue: 04

Page 1 of 2



1. IDENTIFICATION OF SUBSTANCE/PREPARATION AND COMPANY

Product: All those listed above.
Company: Granfix Products Limited • Greenhill Lane • Riddings • Derbys • DE55 4AT
Telephone: 01773 607778 • Fax: 01773 608688

2. COMPOSITION

Product Classification:
Irritant. Contains more than 20% Portland cement in addition to inorganic fillers and organic additives.

Hazardous Ingredient	Classification	%	Index	Risk Phrases
Portland Cement	CAS No. 65997-15-1 EINECS; 266-043-4	>20	Xi	R38, R41

3. HAZARDS IDENTIFICATION

Hazard designation: Xi Irritant.
Hazard to man and the environment: R38 Irritating to skin. R41 Risk of serious damage to eyes. Contains Chromium VI.
May produce an allergic reaction.

4. FIRST AID MEASURES

Inhalation: If irritation occurs, remove to fresh air. If nose/airways become inflamed, seek medical advice.
Skin: Wash thoroughly with soap and water. Remove contaminated clothing. If irritation, pain or other skin trouble occurs, seek medical advice.
Eyes: Irrigate eyes with clean water for at least 15mins. Obtain medical attention as soon as possible.
Ingestion: Do not induce vomiting. Wash out mouth with water and give plenty of water to drink.
If symptoms develop or persist seek immediate medical advice.

5. FIRE FIGHTING MEASURES

Product is not flammable, neither as powder or when set.

6. ACCIDENTAL RELEASE MEASURES

Wear suitable personal protection measures (dust mask, gloves, goggles).
Recover spillages in dry state if possible, avoid dust formation (See section 8).
Do not allow material into water courses and drains.

7. HANDLING/STORAGE

Avoid skin/eye contact. Use in well ventilated areas, especially when mixing.
Wash hands after use.
Store in cool dry conditions and protect from frost.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Suitable gloves should be worn to prevent skin contact.
If dust formation is likely, a suitable dust mask should be worn.
If splashing is a possibility then goggles should be worn.
Occupational exposure must be kept below 10mg/m³/8hour (TWA).
Total Inhalable Dust: 10mg/m³ Inhalable Dust 4mg/m³ (TWA) Respirable Dust

The information given on this safety data sheet is accurate and given in good faith. However, it is given without guarantee as conditions of use and workmanship are beyond the control of Granfix Products. All information is subject to the company's terms and conditions of sale, copies of which are available on request.

SAFETY DATA SHEET - GREY CEMENTITIOUS ADHESIVES

CWFTA • RAPIDSET • FASTSET • FASTSET FLEXIBLE • 1 PART CWFTA • 1 PART RAPIDSET
PORCELAINFIX • POURABLE THICK BED • SLATEFIX • ULTIMATEFLEX
UNIQUE BLUE • UNIQUE RED

Date: 08/08

Issue: 04

Page 2 of 2



9. PHYSICAL/CHEMICAL PROPERTIES

Appearance: Gritty Powder
Density: 1.6 approx.
Solubility: Slightly soluble
pH: Approximately 12 at 20°C saturated solution

10. STABILITY/REACTIVITY

Stable when stored correctly.
Storage in wet/damp conditions may lead to premature hydration of product.
Avoid contact with strong acids and alkalis.

11. TOXICOLOGICAL INFORMATION

Irritant effect on the skin or mucous membranes. Sensitisation/allergic reaction to Chromium VI may occur.
Strong irritant for eyes.
Can cause serious eye damage.

12. ECOLOGICAL INFORMATION

The addition of this product to water will give an alkaline solution which may be toxic to aquatic life.
Do not allow into water courses/drains.

13. WASTE DISPOSAL

Should be disposed of at a suitable landfill site in accordance with Control of Pollution Act 1974 and the Environmental Protection Act 1990.

14. TRANSPORT INFORMATION

This product is not classed as hazardous for the purposes of transportation.

15. REGULATORY INFORMATION

This product has been classified and labelled in accordance with the directives on hazardous materials.
Classification: Irritant.
Reference: Information from raw material suppliers.
Chemicals (Hazard information and packaging) Regulations 2002: Amended 2003.

Risk Phrases	R38 R41	Irritating to skin Risk of serious damage to eyes. Contains Chromium VI May produce an allergic reaction
Safety Phrases	S2 S24/25 S26 S37/39	Keep out of reach of children Avoid contact with eyes and skin In case of contact with eyes, rinse immediately with plenty of water and seek medical advice Wear suitable gloves and eye/face protection

16. OTHER INFORMATION

The product should be used as directed. Consult product data sheet for further details.
This information is given in good faith and is believed to be accurate and complete.
It should be made available to all personnel handling this product.

The information given on this safety data sheet is accurate and given in good faith. However, it is given without guarantee as conditions of use and workmanship are beyond the control of Granfix Products. All information is subject to the company's terms and conditions of sale, copies of which are available on request.